


## The ideal solution for residential gates




- Refined and exclusive design.
- Release system with triangular key.
- Adjustable mechanical stops for memorising the gate run.
- Simplifies connections with a single, three-conductor cable.
- Supporting diecast aluminium half-shells.
- The worm screw is always protected thanks to a specific covering.
- Can work in emergency mode during power outages.
- Self-diagnosing safety devices.
- Tested according to the parameters dictated by current rules and regulations.

### Dimensions (mm)



### Application (mm)



### Limits to use

MODEL	A1824		
Max gate-leaf width (m/ft)	1.8/6	1.5/5	1/3.3
Max gate-leaf weight (Kg/lb)	200/441	215/474	250/550
MODEL	A18230		
Max gate-leaf width (m/ft)	2.2/7.2	1.7/5.6	1/3.3
Max gate-leaf weight (Kg/lb)	200/441	225/496	250/550

● 230 V AC - ● 24 V DC

### Application dimensions (mm/in)

MODEL	A1824 - A18230		
GATE-LEAF OPENING (°)	A	B	C MAX
90°	130/5.11	130/5.11	60/2.36
120°	130/5.11	110/4.33	50/1.96

● 230 V AC - ● 24 V DC

### Technical features

Type	A1824	A18230
Protection rating IP	44	44
Power supply (V - 50/60 Hz)	230 AC	230 AC
Motor Power supply (V - 50/60 Hz)	24 DC	230 AC
Current draw (A)	4 MAX	1.2
Power (W)	100	80
Opening times at 90° (s)	ADJUSTABLE	19
Duty cycle (%)	INTENSIVE USE	50
Thrust (N)	400 ÷ 2000	400 ÷ 2000
Operating temperature (°C/°F)	-20 ÷ +55 / -4 ÷ +131	
Motor thermo protection (°C/°F)	-	150/302

● 230 V AC - ● 24 V DC